

UM-170

Features:

- Resolution: SXGA (1280 x 1024)
- Brightness: 300cd/m²
- Contrast Ratio: 700:1
- Response Time: 6ms (on/off)
- Viewing Angle: 150/140(H/V)



Specification:

Type	17" active matrix TFT SXGA LCD
Pixel Pitch	0.264mm
Response Time (ms) (at 25°C)	6ms (on/off)
Resolution	SXGA (1280 x 1024)
Brightness	300 cd/m ²
Contrast Ratio	700:1
Viewing Angle	150 / 140 (H/V)
Display Color	16.2M
Light Source Life	50,000 hrs. (Min)
Frequency	Fh:31.5 ~ 60.0KHz, Fv:56 ~ 75Hz
Input Signal	0-0.7Vpp, RGB Analog, 75Ω Terminated
DDC	VESA DDC2B
Power Input	Input AC 100~240V 50/60Hz; Output DC 12V 3A
Power Consumption	25~34W (Operation), less than 5W (Standby)
Operating Conditions	Temperature 0 ~ 50 degrees centigrade, Humidity 5% ~ 95%
Certification	FCC, CE, BSMI
Packing Dimensions	430mm(L) × 150mm(W) × 420mm(H)
Weight	3.9Kg (N.W.) 4.2Kg (G.W.)
Video Input	Video and BNC
Audio	2Watts Stereo