

# UM-1901ST

## Features:

- Resolution: SXGA (1280 x 1024)
- Brightness: 330cd/m<sup>2</sup>
- Contrast Ratio: 1300:1
- Response Time: 8ms (on/off)
- Viewing Angle: 178/178(H/V)
- Built-in IST (Image Smoothen Technology)



## Specification:

<b>Type</b>	<b>19" active matrix TFT SXGA LCD</b>
<b>Pixel Pitch</b>	<b>0.294mm</b>
<b>Response Time (ms) (at25°C)</b>	<b>8ms</b>
<b>Resolution</b>	<b>1280x1024</b>
<b>Brightness</b>	<b>330 cd/m<sup>2</sup></b>
<b>Contrast Ratio</b>	<b>1300:1</b>
<b>Viewing Angle</b>	<b>178 / 178(H/V)</b>
<b>Display Color</b>	<b>16.7M</b>
<b>Light Source Life</b>	<b>40,000 hrs. (Min)</b>
<b>Frequency</b>	<b>Fh:31.5~80.0KHz, Fv:56~75Hz</b>
<b>Input Signal</b>	<b>0-0.7Vpp, RGB Analog, 75Ω Terminated</b>
<b>DDC</b>	<b>VESA DDC2B</b>
<b>Power Input</b>	<b>Input AC 100~240V 50/60Hz; Output DC 12V 4 A</b>
<b>Power Consumption</b>	<b>25~34W (Operation),less than 5W (Standby)</b>
<b>Operating Conditions</b>	<b>Temperature 0 ~ 50 degrees centigrade, Humidity 5% ~ 95%</b>
<b>Certification</b>	<b>FCC, CE, BSMI</b>
<b>Packing Dimensions</b>	<b>450mm(Lx455mm(W)×192mm(H)</b>
<b>Weight</b>	<b>7.0Kg (N.W.)8.2Kg (G.W.)</b>
<b>Video Input</b>	<b>Video and BNC</b>
<b>Audio</b>	<b>2Watts Stereo</b>